

Lessons Learned from OSU PacTrans & ODOT UAS Projects

Chase Simpson, Chris Parrish, Dan Gillins,
Matt Gillins

UAS in Transportation Workshop

July 30-31, 2018



3+ Years' of Research Projects



Oregon State University
College of Engineering

1. PacTrans Small project: Cost-effective Bridge Safety Inspections Using Unmanned Aerial Vehicles (UAVs), 2015-2016
2. ODOT SPR 787: Eyes In The Sky: Bridge Inspections With Unmanned Aerial Vehicles, 2015-2017
3. FHWA project with Parsons Brinckerhoff (now WSP): Effective Use of Geospatial Tools in Highway Construction
4. PacTrans Multi-Institution Project: An Airborne Lidar Scanning and Deep Learning System for Real-time Event Extraction and Control Policies in Urban Transportation Networks (OSU & UI), 2016-2019

Specific Project Goals



Oregon State University
College of Engineering

1. Evaluate the performance of UAS-based methods for inspecting bridges
1. Identify which ODOT inspection requirements can and cannot be satisfied with a UAV inspection
2. Provide a cost-benefit analysis of performing UAV inspections for communication towers and bridges
3. Develop procedures/guidelines for how to safely and effectively perform UAS inspections of bridges and communication towers


Test Bridge Inspections



Oregon State University
College of Engineering

Bridges Inspected

- (1) Independence Bridge
- (2) Crooked River Bridge
- (3) Mill Creek Bridge
- (4) St. Johns Bridge
- Preliminary
- (5) Winchester Bridge
- (6) St. Johns Bridge
- Detailed



Test Bridge Inspections



Oregon State University
College of Engineering

Independence Bridge: Sept 2015

Location:

- In Independence, OR

Airframe(s) used:

- DJI Phantom 3 Pro

Flight Objective:

- Familiarize with bridge inspection workflow
- Capture high quality imagery/video for inspection purposes

Details:

- Large deck plate girder bridge
- 675.4 m long
 - Longest span: 46.3 m
- Classified as Fracture Critical



Independence Bridge

Captured Imagery



Oregon State University
College of Engineering



Independence Bridge

Captured Imagery



Oregon State University
College of Engineering



Test Bridge Inspections



Oregon State University
College of Engineering

Crooked River Bridge: July 2016

Location:

- 8 km north of Terrebonne, OR

Airframe(s) used:

- senseFly Albris

Flight Objective:

- Capture high quality imagery for inspection purposes
 - targeting specific areas difficult to inspect using traditional methods
- Create 3D model using SfM

Details:

- Steel Arch Bridge
- 141 m long
 - Longest span: 100 m
- Pedestrian Only



Crooked River Bridge

Captured Imagery



Oregon State University
College of Engineering



Crooked River Bridge

Flight Methods



Oregon State University
College of Engineering





Schematic representation of overlapping images taken from a UAS and the flight path using manual flight mode with sensor assistance (from Javadnejad et al. 2017, with permission)

Crooked River Bridge

Captured Imagery



Oregon State University
College of Engineering




Crooked River Bridge

Captured Imagery




Oregon State University
College of Engineering



Post-Processing

Structure From Motion

- Relatively new photogrammetric approach
 - Leverages advanced image matching algorithms from the field of computer vision
- Many requirements are relaxed, as compared with conventional photogrammetry:
 - Can work with a wide range of viewing geometries and consumer-grade cameras
 - Well suited to UAS imagery!
 - Highly automated, easy to use software



Additional Survey Equipment

Ground Control Survey Equipment




Oregon State University
College of Engineering




(a)



(b)



(c)



(d)

(a) Total station used to position photo identifiable features on bridge Example (c) & (d)




(a) GNSS Antenna occupying an aerial ground control target

Crooked River Bridge

Post-Processing Results – Pointcloud & Orthomosaic



Oregon State University
College of Engineering



An orthophoto of the profile of the Crooked River Bridge produced from processing the images using SfM. (from Javadnejad et al. 2017, with permission)

Test Bridge Inspections



Oregon State University
College of Engineering

Mill Creek Bridge, July 2016

Location:

- 17 km NW of Warm Springs, OR

Airframe(s) used:

- senseFly Albris

Flight Objective:

- Capture high quality imagery for inspection purposes
 - targeting specific areas difficult to inspect using traditional methods

Details:

- Cantilevered Warren deck truss bridge
- 163 m long
 - Longest span: 50 m



Mill Creek Bridge

Captured Imagery



Oregon State University
College of Engineering




Mill Creek Bridge

Captured Imagery



Oregon State University
College of Engineering



Test Bridge Inspections



Oregon State University
College of Engineering

St. Johns Bridge (Prelim Test), Sept 2016

Location:

- St. Johns Portland, OR

Airframe(s) used:

- senseFly Albris
- DJI S900 w/ Sony WX500
(30x optical zoom)

Flight Objective:

- Test use of optical zoom camera
- Capture high quality imagery for inspection purposes
 - targeting specific areas difficult to inspect using traditional methods

Details:

- Metal Riveted Warren deck truss
- Wire Cable Suspension
- 1100 m long
 - Longest span: 368 m



St. Johns Bridge (Preliminary Test)

Captured Imagery



Oregon State University
College of Engineering



St. Johns Bridge (Preliminary Test)

Captured Imagery



Oregon State University
College of Engineering



St. Johns Bridge (Preliminary Test)

Captured Imagery



Oregon State University
College of Engineering



Test Bridge Inspections



Oregon State University
College of Engineering

Winchester Bridge, March 2017

Location:

- Winchester, OR

Airframe(s) used:

- senseFly Albris

Flight Objective:

- Capture high quality imagery for inspection purposes
 - While receiving real-time input from onsite inspectors

Details:

- Warren deck truss bridge
- Southbound bridge of I-5
- 500 m long
 - Longest span: 42 m





Winchester Bridge

Captured Imagery



Oregon State University
College of Engineering



Winchester Bridge

Captured Imagery



Oregon State University
College of Engineering



Winchester Bridge

Captured Imagery



Oregon State University
College of Engineering



Test Bridge Inspections



Oregon State University
College of Engineering

St. Johns Bridge (Detailed Test), April 2017

Location:

- St. Johns Portland, OR

Airframe(s) used:

- senseFly Albris

Flight Objective:

- Capture high quality imagery for inspection purposes
- Week long in-depth inspection
- Test inspecting directly under deck

Details:

- Metal Riveted Warren deck truss
- Wire Cable Suspension
- 1100 m long
 - Longest span: 368 m
- Flight limited to eastern 550 m from center of main span



St. Johns Bridge (Detailed Test)

Captured Imagery



Oregon State University
College of Engineering



St. Johns Bridge (Detailed Test)

Captured Imagery



Oregon State University
College of Engineering



St. Johns Bridge (Detailed Test)

Captured Imagery



Oregon State University
College of Engineering



St. Johns Bridge (Detailed Test)

Captured Imagery



Oregon State University
College of Engineering



St. Johns Bridge (Detailed Test)

Captured Imagery



Oregon State University
College of Engineering



St. Johns Bridge (Detailed Test)

Captured Imagery



Oregon State University
College of Engineering




Test Tower Inspections



Oregon State University
College of Engineering

Towers Inspected

- (1) Woodburn Tower
- (2) Washburn Butte Tower
- (3) Corvallis Maintenance Tower
- (4) Grizzly Mountain Tower




Washburn Butte Tower

Flight Planning



Oregon State University
College of Engineering



Test Tower Inspections



Oregon State University
College of Engineering

Woodburn Tower, April 2016

Location:

- 3 km NNW of Woodburn, OR

Flight Objective:

- Familiarize with tower inspection workflow
- Capture high quality imagery for inspection purposes
- Create orthomosaic of site
- Create 3D model using SfM

Details:

- Owned by Marion County
- A-Frame tower with triangle base
- 5 installed antennas
- 53 m tall



Woodburn Tower

Captured Imagery



Oregon State University
College of Engineering



Woodburn Tower

Captured Imagery



Oregon State University
College of Engineering



Woodburn Tower

Point cloud generated using PhotoScan



Oregon State University
College of Engineering



Test Tower Inspections



Oregon State University
College of Engineering

Washburn Butte Tower, April 2016

Location:

- 6km north of Brownsville, OR

Flight Objective:

- Capture high quality imagery for inspection purposes
- Create orthomosaic of site
- Create 3D model using SfM

Details:

- A-Frame tower with square base
- 8 installed antennas
- 48.8 m tall



Washburn Butte Tower

Collected Imagery



Oregon State University
College of Engineering



Washburn Butte Tower

Collected Imagery



Oregon State University
College of Engineering




Washburn Butte Tower

3D Modeling Results



Oregon State University
College of Engineering





Washburn Butte Tower

3D Modeling Results



Oregon State University
College of Engineering




Washburn Butte Tower

3D Modeling Results



Oregon State University
College of Engineering




Washburn Butte Tower

3D Modeling Results - Organization



Oregon State University
College of Engineering



Properties

▼ Selection

ATP 269887 (Automatic Tie Point)

Number of Images Marked On: 5
Number of Images Visible In: 240
 S^2 [pixel]: 0.6054
Theoretical Error $S(X,Y,Z)$ [m]: 0.022, 0.008, 0.039
Maximal Orthogonal Ray Distance $D(X,Y,Z)$ [m]: -0.003, -0.010, 0.000
Computed Position [m]: 7553143.848, 290671.879, 1229.368

Help

▼ Images

Image Size Zoom Level


EX-01-29880_0123	EX-01-29880_0125	EX-01-29880_0123	EX-01-29880_0123	EX-01-29880_0123
EX-01-29880_0123	EX-01-29880_0123	EX-01-29880_0123	EX-01-29880_0123	EX-01-29880_0123
EX-01-29880_0123	EX-01-29880_0123	EX-01-29880_0123	EX-01-29880_0125	EX-01-29880_0123
EX-01-29880_0123	EX-01-29880_0123	EX-01-29880_0125	EX-01-29880_0123	EX-01-29880_0123
EX-01-29880_0123	EX-01-29880_0123	EX-01-29880_0125	EX-01-29880_0123	EX-01-29880_0123

Washburn Butte Tower

3D Modeling Results - Obstructions



Oregon State University
College of Engineering



Test Tower Inspections



Oregon State University
College of Engineering

Corvallis Maintenance Site Tower, April 2016

Location:

- Corvallis, OR
- ODOTS District 4 maintenance yard

Flight Objective:

- Capture high quality imagery for inspection purposes

Details:

- Rectangular tower with square base
- 2 installed antennas
- 27.4 m tall



Corvallis Maintenance Site Tower

Collected Imagery



Oregon State University
College of Engineering




Corvallis Maintenance Site Tower

Collected Imagery



Oregon State University
College of Engineering



Corvallis Maintenance Site Tower

Collected Imagery



Oregon State University
College of Engineering



Test Tower Inspections

Grizzly Mountain Tower, July 2016



Oregon State University
College of Engineering

Location:

- 23 km NW of Prineville, OR

Flight Objective:

- Capture high quality imagery
- Create 3D model using SfM

Details:

- A-Frame tower with square base
- 9 installed antennas



Grizzly Mountain Tower



Oregon State University
College of Engineering

Findings

- Over 10 towers near mountain summit
- Detected significant frequency interference using a spectrum analyzer
 - 2.4 and 5.0 GHz frequencies
- Interference from nearby Wireless Internet Service Provider (WISP) towers
- Unable to perform any flights
 - Tried all possible radio frequencies available



Cost Benefit Analysis



Oregon State University
College of Engineering

Procedures

1. Establish baseline costs for bridge inspections conducted *without* the use of UAS by compiling existing data from ODOT
 - 33 bridge inspection project budget spreadsheets
2. Determine the percentage of bridges that ODOT inspects that are suitable for UAS inspection
 - Airspace, proximity to populated areas, vegetation, size of bridge, etc.
3. Establish which project cost categories could be reduced (not eliminated) through use of UAS:
 - Personnel time (field and office)
 - Equipment rental/usage (e.g., snooper trucks)
 - Traffic control
 - Travel (including lodging, meals and incidentals)

Cost Benefit Analysis



Oregon State University
College of Engineering


Procedures (cont'd)

4. Estimated annual cost savings = (average cost savings per suitable bridge) × (# of bridges/yr inspected by ODOT) × (percentage of bridges suitable for UAS inspection)
5. Estimate costs:
 - Cost of purchasing 3 UAS
 - Annual maintenance cost
 - Data storage



$$B = \$10,200(730 \times 0.16) = \$1,191,360$$

$$\sum C = \$117,237 + \$4,500 + \$5,700 = \$127,437$$

$$BCR = \frac{\$1,191,360}{\$127,437} \approx 9$$



Legend

-  Bridges Suitable For Inspection By UAS
-  Bridges Not Suitable For Inspection By UAS

Project Key Findings

Operational Considerations



Oregon State University
College of Engineering

- Sensor-assisted and waypoint-assisted flight modes are most useful flight modes for bridge inspection
 - But, unmanned aircraft pilots must be proficient in entirely manual flight, due to the possibility of losing GPS
- UAS with front-mounted, variable-tilt cameras are advantageous for bridge inspection
- Wind condition is the most important environmental variable in UAS bridge inspection
 - Illumination conditions and camera settings (ISO, f-stop and focal length) are critical to obtaining high-quality imagery
 - UAS bridge inspection flight crews should have at least a basic level of expertise in photography

Project Key Findings



Oregon State University
College of Engineering

Overarching conclusions

- UAS can assist to varying degrees in many required elements of a bridge inspection
 - Very well suited for initial and routine inspections and for satisfying report requirements related to geometry and structural evaluation
- Cracks, pack rust, connections, hardware and bearing locations were all determined to be readily-identifiable in the imagery collected in this project, with the recommended flight procedures
- Cost-benefit analysis provides strong indication of positive ROI for implementing UAS in ODOT's bridge inspection program
 - Should be refined as more data becomes available
- UAS are likely to be an increasingly valuable tool to State DOTs in bridge inspection

Acknowledgements



Oregon State University
College of Engineering

- ODOT and PacTrans
- Dr. Joe Li, ODOT Research Coordinator
- Erick Cain, ODOT Bridge Inventory Coordinator
- ODOT TAC:
 - Paul Panzica, ODOT Wireless Network Infrastructure Manager
 - Michael Goff, ODOT Bridge Inspector
 - Mitch Swecker, OR State Aviation
 - Tim Rogers, FHWA
 - Jeff Swanson, ODOT Bridge Section
 - Joe Thomas, ODOT Geometronics Manager / Chief of Surveys
 - Ron Singh, ODOT Chief of Surveys/Geometronics Manager (recently retired)
- OSU graduate students: Kory Kellum, Farid Javadnejad, and Richie Slocum