

Real-time Ocean Observing

WA State ORA briefing 17 March 2010 Jim Thomson



Northwest National Marine Renewable Energy Center





Ongoing Projects (science-focused)

- NSF Ocean Observing Initiative
 - Regional Scale Nodes \$140M to UW
- Canada NEPTUNE project
- Monterey Canyon
- Numerous coastal/local sites










Regional Scale Node



Northwest National Marine Renewable Energy Center







Regional Scale Node

- Shore Station in Pacific City, OR
- xxx km of Backbone Cable
- 6 Primary Nodes
 - 10kV, 9kW, 10 GbE
- 1 Upgradeable Pass-Thru Node


- 2 Coastal Endurance Arrays
- 3 Water Column Profiling Moorings
- xx 10kV, 10GbE Expansion Ports
- xx Secondary Nodes & J-Boxes
- ~xxx ROV–mate Instrument Ports



Northwest National Marine Renewable Energy Center










Northwest National Marine Renewable Energy Center







System integration:

- many components with various power and communication specifications
- trend toward "smart" systems
- Coms: multiplex to ethernet, then send over fiber optic
- Power: step-down supply, galvanic isolation, ground fault monitoring
- Interconnections: ROV


6



Northwest National Marine Renewable Energy Center

Example: ALOHA/MARS mooring testing at Seahurst in 2008








Northwest National Marine Renewable Energy Center



Example: ALOHA/MARS mooring testing at Seahurst in 2008







- PC-104 controller
- 400-48V dc (Vicor)
- MOSFET and deadface switches, software controlled
- Ground fault detection
- 8-port 100baseT Ethernet switch
- Two guest ports
- Can feed 400 V on any port
- 4 channel SIIM boards 12V, RS-232




Northwest National Marine Renewable Energy Center



Example: ALOHA/MARS mooring testing at Seahurst in 2008







Northwest National Marine Renewable Energy Center





Conclusion: real-time ocean observing is here

- Expensive
- Data incomplete, not omniscient
- Data still require analysis/interpretation
- Data does not equal understanding
- Must be guided by rational hypotheses and rigorous probabilities







Application to marine energy

- Needs to be cost-effective
- Needs to be robust– energy sites are harshest
- Need avoid interference with devices
- Needs to be scalable/upgradable







Application to marine energy - conceptual

- Fiber optic to ethernet: real-time observations
- Robust nodal architecture, "daisy chain" interconnections
- Simple retrievals for service/upgrade (independent of device testing) surface connectors, not ROV
- Option to aim/orient sensors

Oregon State

