

The Science and Practice of Sustainable Sites:
**Practical Implementation of
Soil Protection & Restoration**





David McDonald – Seattle Public Utilities
Howard Stenn – Stenn Design
Jim Berger – Port Blakely Communities

*9/27/2011 seminar sponsored by the
WA Chapter of the American Society of
Landscape Architects, UW Botanic Gardens,
and Seattle Public Utilities*

Why a Soil Standard? – Multiple Benefits

- Environmental/sustainability benefits
- Protect/restore stormwater infiltration
 - Bio-filtration of urban pollutants – protect waterways
 - Protect existing vegetation, improve tree & plant growth
 - Reusing organic “wastes” to restore soil function
 - Reduced irrigation use, less need for fertilizers & pesticides

- Value to builder/contractor
- Quicker planting in prepped soil
 - Less plant loss = fewer callbacks
 - Better appearance sells next job

- Value to property owner
- Better plant health & appearance
 - Lower water bills
 - Reduced chemical needs
 - Lower maintenance costs



**Sustainable Sites Initiative
(SITES™) Rating System**

- Prereq. 1.1 Protect farmland soils
- Credit 1.5 Select brown/grey-fields
- Prereq. 2.1 Conduct pre-design site assessment (incl. soil)
- Prereq. 2.2 Use integrated site development process
- Credit 4.4 Minimize soil disturbance (minimize grading)
- **Prereq. 4.3 Create a Soil Management Plan**
- **Prereq. 7.2 Restore soils disturbed during construction**
- Credit 7.3 Restore soils disturbed by previous development
- Prereq. 8.1 Plan for sustainable site maintenance
- Credit 8.3 Recycle organic matter in operations & maintenance

www.sustainablesites.org

**WA State “Post Construction
Soil Quality & Depth” BMP**
*in Dept. of Ecology Stormwater
Manual; coming into local codes*

- Soil management plan showing areas to be protected, or disturbed & restored, and soil/compost/mulch import amounts for each area
- Keep all impacts off protected veg. & soil areas
- Restore disturbed areas by amending with compost, stockpiling & reusing topsoil, or importing amended soil. Scarify subsoil, for 12” uncompacted depth.
- Mulch, and Maintain to replenish organic content.

www.buildingsoil.org

Summary of Soil Best Management Practices

New Construction

- Retain and protect native topsoil & vegetation (esp. trees!)
 - Choose sites to conserve good quality existing veg. & soil
 - Minimize construction footprint
 - Establish veg. & soil protection zones - fence & protect
 - Store and reuse topsoil from site
 - Retain “buffer” vegetation along waterways
- Restore disturbed soils by tilling 2-4” of compost into upper 8-12” of soil. Rip to loosen compacted layers.


Existing Landscapes

- Retrofit soils with tilled-in compost when re-landscaping
- Mulch beds with organic mulches (leaves, wood chips, compost), topdress turf with compost, and mulch-mow to maintain organic content that supports soil ecosystem.

Understanding Soil: development from parent “dirt” & rock

Soil horizons & their evolution

- Substratum (C) or bedrock (R) weathers physically & chemically to subsoil (B)
- Primarily biological processes create topsoil (A) and organic (O) horizons





USDA - NRCS
<http://soils.usda.gov>

5

Sub-Soils in the Puget Sound Basin: Leftovers from glaciers & volcanoes



- glacial till:** unsorted, unstratified mixtures of clay, silt, sand, gravel, and boulders; deposited under ice, or in moraines
- hardpan:** till compacted under glacier
- outwash soils:** layers sorted by particle size by water - sand / gravel / rocks
- lake/marine bed soils:** clay or silt that settled out in lakes & estuaries



- volcanic ash:** light, fertile, holds moisture - mostly blown east of Cascades
- mudflows:** mixed size, compact - like till

Learn about Puget Sound soils at:
www.puyallup.wsu.edu/soilmgmt/Soils.htm

6

Glacial till

- May be piled, uncompressed and unsorted, in *moraines* at edge or terminus of glacier
- *Basal till* from under the glacier (1/2 mile of ice over Seattle!) has been compressed into **hardpan**
- Good for foundations, but low permeability and hard for roots to penetrate



7

Glacial outwash

- May be sorted boulders, gravel
- ...sand and fines.....
- Or a mix!



8

Lake beds, lenses, and layers

- Silts and clays settle out...
- And then may be overlain in lenses with sand or gravel from succeeding outwash
- Grey-yellow color when saturated and anaerobic
- Great for farming, (best nutrient capacity) but unstable in slopes or foundations!



9

Volcanic ash or mudflows

- Tephra (ash) – light, fertile, holds moisture, erodable
- Mudflow – compact, mixed fines and boulders, low permeability, looks and acts like basal till, but more fertile



10

Alluvial soils


- Flat, loamy deposits in river floodplains (or ancient rivers)
- Best for farming, often wasted on development because they're flat



11

Layers upon layers... ignore them at your peril!

- Sandy outwash over compacted basal till hardpan
- Thin soil over bedrock
- Clay lenses over hardpan, or inter-layered with sand (unstable!)



12

Disturbed soils in urban areas



- Topsoil layer removed
- Compaction
- Subsoil (or worse) fill layers.
- Debris or toxins?




Soil Texture = mineral particle size (sand and finer particles)

Ribbon + feel test:

Moisten soil, roll between hands, then squeeze out with thumb

- Sand: no ribbon, grainy
- Sandy loam: ½ inch ribbon
- Loam: thick 1 inch ribbon
- Silt: makes flakes rather than ribbon
- Silty clay loam: thin, breaks easily, floury feel
- Sandy clay loam: stronger, grainy
- Clay: long (3 inch) ribbon, smooth feel




Understanding soil: texture, structure, & pore space (thus infiltration)

Soil components:

- “The Dirt”
(mineral part)
 - sand
 - silt
 - clay
- Air and Water
- Organic Matter and Soil Life
(create aggregates & pores)


Good soil is about
- half mineral
- half space (air & water)
- plus a smaller but essential amount of organic matter & soil life



“Loam” is a mix of sand, silt, clay and organic, formed over time by nature


Understanding Soil Biology *Soil life provides essential functions*

Soil is alive!




Common organisms in the soil foodweb


• Bacteria



• Fungi



• Protozoa



• Nematodes



• Arthropods




• Earthworms



Restoring soil life, to restore soil functions

Soil organisms create:

- soil structure
- fertility = nutrient cycling
- plant disease protection
- biofiltration
- erosion control
- stormwater detention



Compost kickstarts the soil ecosystem!
(Provides food and home for organisms)

How does soil life create soil structure?

- Bacteria secretions glue clays, silts and sands together into micro-aggregates.
- Micro-aggregates are bound together by fungal hyphae, root hairs and roots.
- Spaces are made by moving arthropods & earthworms, and decaying roots.
- Only when all organisms are present can roots and water move into the soil with ease.





S. Rose & E.T. Elliott

19

How does soil life provide fertility (nutrient cycling)?

- Soil foodweb stores nutrients in living & dead organic matter
- Nutrients are released in root zone as organisms eat and excrete “waste” (nitrogen, etc.)
- Mycorrhizal fungi bring nutrients and water to roots of plants




Dr. Michael P. Amarantus, Mycorrhizal Applications Inc.

20

How does soil life provide plant disease protection?

Diversity ⇒ predation, parasitization & competition with the few disease-causing organisms

- Bacteria cover leaf surfaces, block infection
- Ecto- and endo-mycorrhizae prevent root infection
- Many organisms prey on the few disease-causing organisms




How does soil life filter out urban pollutants?

- Creates structure
- Breaks down hydrocarbons, pesticides
- Converts fertilizers to stable forms, so they are available to plants but won't wash away
- Binds heavy metals in soil, so they don't wash into streams




How does soil life control erosion?

- Creates pore spaces, increases infiltration
- Sticks soil particles & aggregates together with bacterial slime, fungal hyphae, & root hairs (bigger aggregates are harder to move) → “aggregate stability”
- Promotes rapid plant growth & deep root development



How does soil life provide stormwater detention / infiltration?

- Builds soil structure, moisture-holding capacity
- Increases surface porosity



UW trials, turf on glacial till soil

Compost-amended till soil – up to 50% reduction in storm water runoff



How can we enhance & restore soil biodiversity, to improve plant growth, water quality, and reduce runoff?

- Protect existing soil & vegetation where possible
- Prevent /reduce compaction (keep heavy machinery off)
- Reduce intensive use of pesticides & soluble fertilizers
- Incorporate compost into soil to feed soil life



organic matter + soil organisms + time
creates ⇒
soil structure, biofiltration, fertility, & stormwater detention

Site selection & planning to protect good soils

- Select previously disturbed sites instead of greenfields.
- Infill to enhance communities, connect with transit.
- Start early to identify site values, and locate development on site to maximize protection of best soils, trees, habitat, natural drainage, etc. Involve arborists, soil & habitat experts. Sell these values to developers/ decision makers.
- Plan to minimize grading, soil export/import.

THE SUSTAINABLE SITES INITIATIVE
Select locations to preserve existing resources and repair damaged systems

Prerequisite 1.1: Limit development of soils designated as prime farmland, unique farmland, and farmland of statewide importance

Prerequisite 1.2: Protect floodplain functions

Prerequisite 1.3: Preserve wetlands

Prerequisite 1.4: Preserve threatened or endangered species and their habitats

Credit 1.5: Select brownfields or greyfields for redevelopment (5–10 points)

Credit 1.6: Select sites within existing communities (6 points)

Credit 1.7: Select sites that encourage non-motorized transportation and use of public transit (5 points)

Protecting soil & vegetation during construction

- Fence *vegetation & soil protection zones*
- Inform all contractors & subs: no stockpiling, trailers, etc.
- If temporary vehicle access required, place steel plates over 6” coarse wood chip.



Street tree protection measures in action



Box trucks, protect root zones from compaction

- Avoiding cutting roots – by using air spade & vactor, or boring to place conduits.




Sustainable Sites soil requirement:

THE SUSTAINABLE SITES INITIATIVE

Prereq. 7.2 Restore soils disturbed during construction

Ecology Stormwater Mgmt. Manual for Western WA:

BMP T5.13 Post-Construction Soil Quality and Depth




- Retain & protect native soil and vegetation wherever possible
- Areas cleared or graded required to restore min. soil depth:
 - Organic matter content (SITES ≥ 3%; Ecology ≥ 10% planting beds, 5% for turf – driven by stormwater performance in NW)
 - SITES: ≥ 12-inch amended soil depth. Use native topsoil, amend existing soil with compost, or import topsoil blend.
 - Ecology: Subsoil scarified 4 inches below 8-inch amended soil, for 12" finished uncompacted depth
 - Protect amended soil from compaction
 - Mulch after planting
 - Maintenance practices to replenish organic content

29

Manual for Implementing BMP T5.13

- also referenced by SITES 4.3 Soil Mgmt. Plan and 7.2 Restore Soils Disturbed by Construction



- Manual developed regionally with experts
- Develop a “Soil Management Plan” for each site
- Four options for soil management (can use 1 or more / site):
 - 1) Retain undisturbed native soil & vegetation, protect from compaction
 - 2) Amend existing soil in place with compost
 - 3) Stockpile topsoil prior to grading, and reuse on site (amend if needed)
 - 4) Import topsoil meeting organic matter content requirements
- Choose pre-approved or custom calculated amendment rates
- Simple field inspection and verification procedures


Available www.soilsforsalmon.org or www.buildingsoil.org

30



How to Select Compost

Know your supplier!



- Field tests:
 - earthy smell - not sour, stinky, or ammonia
 - brown to black color
 - uniform particle range
 - stable temperature (does not get very hot if re-wetted)
 - not powdery or soaking wet
- Mfr.-supplied info:
 - Permitted WA composting facility – meets WAC 173-350 requirements
 - Meets US Compost Council (STA) “Seal of Testing Assurance”
 - C:N ratio
 - Weed-seed trials
 - Nutrients, salinity, contaminants
 - Size: “screen”, % fines
- Soil/compost lab test info:
 - Nutrients
 - Salinity
 - pH
 - % organic content (OM)

31

Carbon to Nitrogen ratio of composts

- For turf & most landscapes
C:N ratio of 20:1 to 25:1 - good nutrient availability for first year of growth (no other fertilizer needed)
- For native plants and trees
C:N ratio of 30:1 to 35:1, and coarser (1” minus screen)
 - less Nitrogen better for NW natives, discourages weeds
 - for streamside, unlikely to leach nitrogen

32

Clearing up the confusion about “% organic”

“% Soil Organic Matter Content” in lab soil tests is by loss-on-ignition method

- Most composts are 40-60% organic content by this method



Recommended soil amendment rates
(for low-organic soils or sand-compost topsoil mixes):

- 5% Soil Organic Matter Content for Turf
=15-25% compost amendment by volume
- 10% Soil Organic Matter Content for Landscape Beds
=30-40% compost amendment by volume

33



Compost Application Methods

Compost application & incorporation methods:

- Blowing
- Spreading
- Tilling / ripping
- Blending off-site



34

Blowing & spreading

- Blower trucks
- Various construction grading equipment
- Other equipment :
golf course & farm spreaders



35

Issaquah Highlands – the big scale



36

Incorporating amendments into soil

- Range of equipment for different-sized sites
- Till in to 8" depth
- If compacted, rip to 12" depth before/while amending



Stockpile site soils & amend, after road & foundation work

- Allows mass grading
- Can reduce hauling & disposal costs
- Set grade to allow re-application of topsoil & allow for settling
- Amend stockpile to spec offsite, or after reapplication
- Spread after concrete work
- Rip in first lift, to reduce sub-grade compaction




Importing "Topsoil"

- "Topsoil" is not a defined, regulated product. Topsoil products often include subsoil, uncomposted organic material, land-clearing and construction debris...
- Best to use mixes containing only clean compost and mined sand or "sandy loam" as defined by USDA.
- Important to avoid clay that can inhibit drainage – spec <5% passing #200 sieve
- See Seattle/WSU/PSP "Bioretention Soil" specification at www.seattle.gov/util/GreenInfrastructure



Compost Based Erosion Control BMPs

- EPA-approved BMPs: **blankets, berms, and socks** see www.buildingsoil.org
- "2 for 1" – use compost for erosion control, then till in at end to meet soil BMP:
 - No disposal costs
 - Faster planting, better growth
- Costs: blankets similar to rolled products, but savings on disposal, plus 2 for 1 benefits



"2 for 1" – construction erosion control and soil quality BMPs are met with compost at Issaquah Highlands.

Combine methods as needed
for best water quality and flow control

WsDOT - Protecting Wetland Area from I-5 Runoff



MULCHING: after planting, & annual maintenance

BENEFITS OF MULCHES:

- Limit weed growth, & make weeds that sprout easy to pull.
- Conserve water, moderate soil temperature, and reduce erosion.
- Replenish soil organic matter, enhancing soil biodiversity, structure, and nutrient cycling = increased plant vigor.



WHAT: Arborist Wood Chip Mulch is best – see spec 9-14.4(5)

www.seattle.gov/util/Engineering/Standard_Plans_8_Specs/index.asp

- Bark can inhibit air & water, doesn't build soil
- Coarse compost builds soil but doesn't suppress weeds.

HOW MUCH: 2-4 inches wood chips, replenish annually until plant canopy closes.

Developing A Soil Management Plan (SMP)

- A scale-drawing identifying areas where each soil treatment option will be applied.
- A completed SMP form identifying treatment options, amendment products and calculated application rates for each area.
- Copies of laboratory analyses for compost and topsoil products to be used, with OM content and C:N

Model SOIL MANAGEMENT PLAN for BMP 15.13
Created by: 10/10/2010 or visit: www.wsdot.wa.gov

Page 7 of 7 pages

PROJECT INFORMATION
Complete all information on page 1 only. Add address and permit number on additional pages.

Site Address: Lot No. _____ Permit Number: _____
Project Name: _____ Permit Holder: _____
Mailing Address: _____ Phone: _____
Contract Number: _____
Plan Proposed By: _____

ATTACHMENTS REQUIRED TO BE SUBMITTED WITH THIS PLAN
See Plan showing: In color: _____ Areas of disturbed native vegetation (no amendment required)
_____ New planting beds and soil areas (amendment required)
_____ Type of soil improvement proposed for each area
_____ Soil test results (required if proposing custom amendment rates)
_____ Provide test results for ground amendments

AREA 1: (shaded match area 1 on Site Plan)
PLANTING TYPE: _____ Unimproved native vegetation
_____ Disturbed site

SQUARE FOOTAGE OF THIS AREA: _____ square feet
SCAFFOLDING: _____ inches (depth of scaffolding needed to achieve finished soil 12" below grade)


PRE-APPROVED AMENDMENT METHODS
Liquid topsoil: _____ cu. yds. per 1,000 sq. ft. PRODUCT: _____ QUANTITY: _____ CU. YDS.
Amended with compost: _____ cu. yds. per 1,000 sq. ft. PRODUCT: _____ QUANTITY: _____ CU. YDS.
Soil and sand: _____ cu. yds. per 1,000 sq. ft. (needed to cover this area to designated depth) PRODUCT: _____ QUANTITY: _____ CU. YDS.
CUSTOM AMENDMENT: _____ Attach test results and calculations.
Liquid topsoil: _____ cu. yds. per 1,000 sq. ft. PRODUCT: _____ QUANTITY: _____ CU. YDS.
Amended with compost: _____ cu. yds. per 1,000 sq. ft. PRODUCT: _____ QUANTITY: _____ CU. YDS.
Soil and sand: _____ cu. yds. per 1,000 sq. ft. (needed to cover this area to designated depth) PRODUCT: _____ QUANTITY: _____ CU. YDS.

NEEDS: _____
N 2.1. Compost: require 2 inch match depth
_____ cu. yds. of match: _____ cu. yds. of match: _____

TOTAL AMENDMENT TOPSOIL MULCH FOR ALL AREAS: _____
1. Topsoil: _____ cu. yds. _____
2. Topsoil: _____ cu. yds. _____
3. Topsoil: _____ cu. yds. _____
4. Topsoil: _____ cu. yds. _____
5. Topsoil: _____ cu. yds. _____
6. Topsoil: _____ cu. yds. _____
7. Topsoil: _____ cu. yds. _____
8. Topsoil: _____ cu. yds. _____
9. Topsoil: _____ cu. yds. _____
10. Topsoil: _____ cu. yds. _____
11. Topsoil: _____ cu. yds. _____
12. Topsoil: _____ cu. yds. _____
13. Topsoil: _____ cu. yds. _____
14. Topsoil: _____ cu. yds. _____
15. Topsoil: _____ cu. yds. _____
16. Topsoil: _____ cu. yds. _____
17. Topsoil: _____ cu. yds. _____
18. Topsoil: _____ cu. yds. _____
19. Topsoil: _____ cu. yds. _____
20. Topsoil: _____ cu. yds. _____
21. Topsoil: _____ cu. yds. _____
22. Topsoil: _____ cu. yds. _____
23. Topsoil: _____ cu. yds. _____
24. Topsoil: _____ cu. yds. _____
25. Topsoil: _____ cu. yds. _____
26. Topsoil: _____ cu. yds. _____
27. Topsoil: _____ cu. yds. _____
28. Topsoil: _____ cu. yds. _____
29. Topsoil: _____ cu. yds. _____
30. Topsoil: _____ cu. yds. _____
31. Topsoil: _____ cu. yds. _____
32. Topsoil: _____ cu. yds. _____
33. Topsoil: _____ cu. yds. _____
34. Topsoil: _____ cu. yds. _____
35. Topsoil: _____ cu. yds. _____
36. Topsoil: _____ cu. yds. _____
37. Topsoil: _____ cu. yds. _____
38. Topsoil: _____ cu. yds. _____
39. Topsoil: _____ cu. yds. _____
40. Topsoil: _____ cu. yds. _____
41. Topsoil: _____ cu. yds. _____
42. Topsoil: _____ cu. yds. _____
43. Topsoil: _____ cu. yds. _____
44. Topsoil: _____ cu. yds. _____
45. Topsoil: _____ cu. yds. _____
46. Topsoil: _____ cu. yds. _____
47. Topsoil: _____ cu. yds. _____
48. Topsoil: _____ cu. yds. _____
49. Topsoil: _____ cu. yds. _____
50. Topsoil: _____ cu. yds. _____
51. Topsoil: _____ cu. yds. _____
52. Topsoil: _____ cu. yds. _____
53. Topsoil: _____ cu. yds. _____
54. Topsoil: _____ cu. yds. _____
55. Topsoil: _____ cu. yds. _____
56. Topsoil: _____ cu. yds. _____
57. Topsoil: _____ cu. yds. _____
58. Topsoil: _____ cu. yds. _____
59. Topsoil: _____ cu. yds. _____
60. Topsoil: _____ cu. yds. _____
61. Topsoil: _____ cu. yds. _____
62. Topsoil: _____ cu. yds. _____
63. Topsoil: _____ cu. yds. _____
64. Topsoil: _____ cu. yds. _____
65. Topsoil: _____ cu. yds. _____
66. Topsoil: _____ cu. yds. _____
67. Topsoil: _____ cu. yds. _____
68. Topsoil: _____ cu. yds. _____
69. Topsoil: _____ cu. yds. _____
70. Topsoil: _____ cu. yds. _____
71. Topsoil: _____ cu. yds. _____
72. Topsoil: _____ cu. yds. _____
73. Topsoil: _____ cu. yds. _____
74. Topsoil: _____ cu. yds. _____
75. Topsoil: _____ cu. yds. _____
76. Topsoil: _____ cu. yds. _____
77. Topsoil: _____ cu. yds. _____
78. Topsoil: _____ cu. yds. _____
79. Topsoil: _____ cu. yds. _____
80. Topsoil: _____ cu. yds. _____
81. Topsoil: _____ cu. yds. _____
82. Topsoil: _____ cu. yds. _____
83. Topsoil: _____ cu. yds. _____
84. Topsoil: _____ cu. yds. _____
85. Topsoil: _____ cu. yds. _____
86. Topsoil: _____ cu. yds. _____
87. Topsoil: _____ cu. yds. _____
88. Topsoil: _____ cu. yds. _____
89. Topsoil: _____ cu. yds. _____
90. Topsoil: _____ cu. yds. _____
91. Topsoil: _____ cu. yds. _____
92. Topsoil: _____ cu. yds. _____
93. Topsoil: _____ cu. yds. _____
94. Topsoil: _____ cu. yds. _____
95. Topsoil: _____ cu. yds. _____
96. Topsoil: _____ cu. yds. _____
97. Topsoil: _____ cu. yds. _____
98. Topsoil: _____ cu. yds. _____
99. Topsoil: _____ cu. yds. _____
100. Topsoil: _____ cu. yds. _____

1: Review Landscape and Grading Plans


Working with plans, check the soil in each area to assess how grading will impact soil conditions and potential for reuse of topsoil excavated for building foundations, stormwater detention facilities and pavement.



Soil Treatment Options	Amendment Rate Options
Option 1. Retain undisturbed native vegetation and soil, and protect from compaction during construction.	SITES™: Min. 3% OM = 1.5" compost into 12" soil
Option 2. Amend existing soil at pre-approved or custom calculated rates based on soil and amendment tests.	WA DOE: Pre-approved Amendment Rate Turf: Mix 1.75 compost into 8" soil. Beds: Mix 3" compost in to 8" soil.
Option 3. Import topsoil mix of sufficient organic content and depth.	Pre-Approved Topsoil Import Rate Place 8 inches of topsoil (or enough to provide 8 inch depth with existing soil). Turf: 5% OM = 20-25% compost + 75-80% sand or loam. Beds: 10% OM = 35-40% compost + 60-65% sand or loam.
Option 4a. Stockpile native topsoil during grading, and reapply after construction. (import soil if needed to achieve depth).	Custom-Calculated Rate Test soil and amendment for organic content and density to determine amendment rate needed to achieve organic content
Option 4b. Amend stockpiled soil if needed to meet 5-10% o.m.	

2. Identify Areas Suitable for Each Option

- Establish *vegetation and soil protection zones* where “native” plants and duff– will be left undisturbed and protected from compaction during construction.
- Excavated or graded topsoil suitable for stockpiling and reuse on site.
- Compacted layers less than 12 inches deep (after grading) – require scarification or soil import.
- Existing organic content in soil to be retained or stockpiled and reapplied – reduced amendment rate.



3. Tests to Conduct for Custom Calculated Amendment Rates

If planning to use calculated amendment rate, sample and test soil. Request compost test results from supplier.

Soil

- Bulk density
- Percent organic matter

Compost


- Bulk density
- Percent organic matter
- Moisture content
- Carbon to nitrogen ratio

Sampling and calculations must be performed by licensed Soil Scientist, Geologist, Civil Engineer or Landscape Architect.

47

4. Select Amendment Options

Outline areas where each amendment option will be applied on plan. Assign each area a letter (A, B, C...) on the plan and Soil Management Plan form.




48

12

5. Calculate Amendment, Topsoil & Mulch Volumes on Soil Management Plan Form

- For Pre-Approved Amendment Rates: Calculate the square footage of each area, and complete calculations for each area to convert inches of amendment into cubic yards.
- To Compute Custom Calculated Amendment Rates: Use soil and amendment test results, and the Model Amendment Rate Calculator.
- List products on the Soil Management Plan form.
- Procure recent product test sheets showing that compost or other organic materials specified meet requirements.



Amendment calculators at:
www.buildingsoil.org
www.soilsforsalmon.org
or (King County example)
http://out.kingcounty.gov/solitheaste/compost_calculator.htm
or (Seattle soil amendment std. plan)
http://www.seattle.gov/dest/00492_Site/mwaterCodeForms/

Verification of Post-Construction Soil Quality and Depth BMP



Inspections



Verification



Dispute Resolution

Who Will Verify BMP?

Primary

- Code Enforcement Inspector
- May be assigned to Licensed Landscape Architect

Independent Inspection to Resolve Disputes

- Certified Soil Scientist, Crop Advisor or Agronomist
- Licensed Landscape Architect, Civil Engineer or Geologist

Suggested Inspection Procedures

- Pre-Grading Inspection
- Grading Progress Inspection
- Post-Construction Inspection
- Mulch Verification

Exact number of inspections will vary between jurisdictions and project type.

Example verification forms at www.soilsforsalmon.org

A thumbnail image of a 'Field Verification Form' titled 'Field Verification Form Post-Construction Soil Standard (BCC 10.02)'. The form is divided into several sections with checkboxes and lines for text entry, including 'Project Information', 'Verify Soil Treatment for Areas Identified on Site Plan', 'Inspect and Verify', and 'Inspect Delivery Tickets and Test Results'.

Suggested Inspection Procedures

- Pre-Grading Inspection
- Grading Progress Inspection
- Post-Construction Inspection
- Mulch Verification


Exact number of inspections will vary between jurisdictions and project type.

Example verification forms at www.soilsforsalmon.org

A detailed 'Field Verification Form' from the 'King County Department of Public Works'. The form is divided into several sections: 'Project Information' (Project Name, Address, Date, Inspector, etc.), 'Inspection Log' (a table for recording inspection dates and results), and 'Inspection Details' (a series of checkboxes and text boxes for recording specific findings related to soil management, erosion control, and mulch application). The form is titled 'Field Verification Form' and 'Post construction Soil Standard (MCC 14.001)'. It includes a header for 'King County' and a footer for 'Department of Public Works'.

Inspection / Verification Supplies

- Field Verification Form
- Soil Management Plan
- Site drawing
- Shovel
- Tape measure



Pre-Grading / Grading Progress Inspection

- Verify native soils & vegetation delineation and protection per SMP
- Review SMP with general contractor and/or grading equipment operator
- Verify erosion controls in place
- Verify excavation & stockpiling of native soils consistent with SMP
- Check sub-grades consistent with SMP


Post Construction (prior to planting)

- Compare conditions to SMP / drawings
- Confirm volumes on amendment delivery tickets match approved SMP
- Dig test holes to check depth of amended soil & scarification
- Use shovel test to check uncompacted depth in multiple locations




Dig Test Holes to Check Depth of Amended Soil & Scarification

- At least three 12 inch deep test holes (3 per acre minimum) for each treatment
- 8" depth of amended soil (excluding mulch layer)
- Scarified subsoil



Check Soil Depth

- Use shovel or rod “driven only by inspectors weight” to test for compaction
- Test 10 locations per landscaped acre (10 minimum per site).



Dispute Resolution

- Organics verified using Loss On Ignition method
- No analytical method to verify scarification






Field Inspection and Verification guide available at www.soilsforsalmon.org (in *Building Soil* manual and as separate PDF)

Issaquah Highlands

1000 ft. elevation change, dense “urban village” development.
700 acres developed, 1400 acres deeded to King County as permanent open space.









Project Sequencing

- ◆ GMA-vs-Soil Conservation
 - GMA mandates higher density
 - Less opportunity for conservation on smaller lots and compact development
 - There may be no native soil & vegetation to conserve
 - Restoration more appropriate?

Soils Planning and Coordination

◆ Challenges

– Is the soils plan practical?

◆ Dirt Cheap??? Hauling dirt is expensive!

◆ Room to stockpile topsoil?

◆ Cost

– Stockpile-vs-export/import:

◆ Stockpile & reuse is cheaper, if there's room

◆ Cost of compost

– Save compared to hauling more topsoil

RESULTS





Park establishment, using amended stockpiled topsoil.



Stormwater pond as amenity: compost-amended soil makes the difference.





Hydroseed and straw mulch: the next spring – no growth.



Same slope, same seed, but applied with compost blanket: next spring – slope's stabilized, job's done.



Compost and seed blown over rock road-cut face: superior erosion protection, and long-term plant success.

The green sells the project. Good soil makes the green.



Construction Sequencing for Soil Protection

Design phase

- Choose site & program to minimize impacts.
- Identify vegetation & soil protection areas; verify they fit into development program and site access routes.
- Identify areas to be graded, and soil restoration options. Calculate compost amendment, topsoil, & mulch on Soil Management Plan.

Site grading through construction phases

- Communicate Soil Management Plan to managers & contractors.
- Fence vegetation & soil protection areas prior to first disturbance.
- Stockpile topsoil to be reused with breathable cover.
- Grade below finish grade to allow placing topsoil/amendments.
- Compost based erosion BMPs can be reused as soil amendment.
- Place rock road bases ASAP and keep vehicle traffic on them.

Construction Sequencing for Soil Restoration (cont.)

Post construction, pre-planting phase

- Amend all disturbed soil areas or place amended topsoil.
- Avoid tilling through tree roots, or raising soil height on trunk.
- Plan for amended soil to settle, by placing amended soil higher, or retain/import amended topsoil to meet final grades.

After planting, end of project phase

- Remove protection area barriers. Have arborist evaluate trees for stress/ need for remediation.
- Mulch all planting beds (& tree root zones with exposed soil).
- Protect amended/restored soils from compaction.
- Communicate a landscape management plan to property owners.

Learn More:

- Protect existing soils and vegetation where possible.
- Restore natural functions in disturbed soils, by reducing compaction and using organic amendments.



www.SustainableSites.org



www.BuildingSoil.org



www.SoilsforSalmon.org